

SUPER 400 SLURRY PUMP



BUILT AS THE NAME SUGGESTS



The Hi-Spec Super 400 Slurry Pump is one of the highest performing pumps on the market today. With a power requirement of only 75 h.p., it creates one of the highest outputs available, which depending on slurry density, can vary from 3,000 gallons (13,600 ltrs) to 4,000 gallons (18,200 ltrs) per min. Easily making the Hi-Spec Super 400 Slurry Pump a market leader.

ADVANTAGES

Each Super 400 Slurry Pump comes complete with a unique quick attachment pick-up system, making it a fast and easy task to both link and unlink the pump to and from the tractor. Changing from the transport to working position requires no disconnection of the P.T.O. shaft, making travel from slurry tank to slurry tank possible without the hassle of disconnecting the P.T.O.

The Super 400 Slurry pump is suitable for use in both open type ground level tanks and slatted house tanks.



FEATURES

- Fully galvanised finish.
- Unique external screw type rotor prevents blockages and increases output.
- Can be used for top filling slurry wagons/vacuum tankers etc.
- Uses a blank off system which makes it possible to change over from mixing to filling at full revs.
- Requires no disconnection of P.T.O. shaft when entering or leaving tanks.
- Jet revolves through a wide arc, allowing slurry to be mixed in any direction including underneath the tractor.
- Safety Platform.
- Depth control is hydraulically operated from the tractor seat.
- Shear pin fitted to the main P.T.O. shaft to prevent breakage or damage to the pump.
- 110 h.p. heavy duty gearbox.

Optional:

- Top fill pipe assembly.

●
Built to last

●
Simple, reliable

& Strong

HI-SPEC ENGINEERING LTD.

Station Road

Bagenalstown

Co. Carlow, Ireland

Tel: (059) 9721929/9721992

Fax: (059) 9721980

Tel. UK & International

(00 353 59) 9721929/9721992

Fax: UK & International:

(00 353 59) 9721980

Website: www.hispec.net

E-mail: sales@hispec.net